

# VISKON-AIRE\*

Air Filter Products

## Meets New EPA Regulations!

### Series XHD Filters - 22 Grams

Premium product for maximum performance and protection!

### Series 107X Filters - 18 Grams

The industry's best all around value!

### SG-15 Filters - 15 Grams

Prudent choice when cost is paramount!

**10% OFF**  
On All Fiberglass  
Paint Arrestors!

**All Paint Arrestors Are Waterborne  
Compatible & 98+% Efficient!**

See local jobber for pricing.

EPA test reports available at  
[www.viskon-aire.com](http://www.viskon-aire.com)

# VISKON-AIRE\*

Air Filter Products

## Spray Booth Maintenance Guidelines. **DID YOU KNOW?**

### Supply Air/Intake Filter Change-Out Guidelines:

- Crossdraft booth intake filters: every 30 to 40 paint jobs or when the indicator dot appears dramatically white
- Downdraft pre-filters: every 3 months or 200 hours of operation
- Ceiling filters: every 800 to 1200 hours of operation or when the indicator dot appears dramatically white

### Exhaust Air/Paint Arrestors Change-Out Guidelines:

- Crossdraft arrestor pads: every 15 to 25 paint jobs
- Downdraft arrestor rolls: every 50 hours of operation
- Do not clean filters with high pressure air
- In general filter change-out times vary with object being painted, velocity, distance from spray gun to the arrestor bank and the type of spray booth being used

### Spray Booth Regular Maintenance Guidelines:

- Sponge clean walls daily
- Check fans and motors monthly, cleaning as needed
- Wash floors daily
- Run booth for 30 minutes after filter change-outs



More information at  
[www.viskon-aire.com](http://www.viskon-aire.com)